

Remote camera control	
Protocol	IPv4, RS-422 (Panasonic AW series protocol)
Connection	Serial: Up to 5 cameras / IP: Up to 100 cameras (Up to 100 when Serial and IP are used together)
Adjustment functions	Pan/tilt, Zoom, Focus, Iris, Gain, Pedestal, Shutter, Detail, White Balance (Auto, R/B Gain), Black balance (Auto, R/B Pedestal), Switch scene files
Preset memory	Up to 100
Switcher control	
Connection	IP: 1
Switcher supported	AW-HS50N
Linkage	Camera information display, TALLY information imported, BUS material selection (AUX / PVW / PinP / KEY-F), Parameter changes (Pan/tilt lever, Zoom button)
Interface	
TALLY/GPI	TALLY input x 5 channels
	GPI INPUT x 4 channels
	GPI OUTPUT x 4 channels
	D-sub 15 pin (female x 1)
LAN	10BASE-T/100BASE-TX (for IP control)
	RJ45 x 1
Pan/Tilt head	RS422 (for Serial control)
	RJ45 x 5
General	
Power requirement	DC 12V \pm 10 % (AC adapter provided)
Power consumption	2.0 A
Operating temperature	0°C to +40°C
Operating humidity	10% to 90% (no condensation)
Weight	1.1 kg (without options)
Dimensions (W x H x D)	210 x 67 x 177 mm (excluding protrusions)

Note: Weight and dimensions shown are approximate. Specifications are subject to change without notice.